


PS220/PS230 FIT METAL PUMP


25 mm (1") Pump
Maximum Flow Rate:
212 lpm (56 gpm)



PS230 METAL

DIMENSIONAL DRAWINGS

PS220 Metal | Center-Ported



DIMENSIONS

ITEM	METRIC (mm)	STANDARD (inch)
A	322	12.7
B	36	1.4
C	163	6.4
D	254	10.0
E	287	11.3
F	38	1.5
G	417	16.4
H	71	2.8
J	140	5.5
K	155	6.1
L	206	8.1
M	173	6.8
N	104	4.1
P	127	5.0
R	10	0.4


LW0368 REV. A

PUMP DATA

Specifications:

Ship Weight..... Aluminum 19 kg (41 lb)
Ductile Iron 29 kg (64 lb)
316 Stainless Steel 31 kg (68 lb)
Alloy C 36 kg (80 lb)
Air Inlet 13 mm (1/2")
Liquid Inlet..... 25 mm (1")
Liquid Outlet..... 25 mm (1")

PS230 Stainless Steel



DIMENSIONS

ITEM	METRIC (mm)	STANDARD (inch)
A	373	14.7
B	69	2.7
C	195	7.6
D	287	11.3
E	340	13.4
F	343	13.5
G	71	2.8
H	417	16.4
J	71	2.8
K	140	5.5
L	188	7.4
M	206	8.1
N	173	6.8
P	104	4.1
R	127	5.0
S	10	0.4
T	203	8.0

DIN FLANGE

U	85 DIA.	3.1 DIA.
V	115 DIA.	4.3 DIA.
W	14 DIA.	0.6 DIA.

LW0366 REV. A

WILDEN®

22069 Van Buren Street
Grand Terrace, CA 92313-5607 USA

O: +1 (909) 422-1730 F: +1 (909) 783-3440
www.psgdover.com


PSG
a **DOVER** company
psgdover.com

PS220/PS230 FIT METAL PUMP

PERFORMANCE

PS220/PS230 METAL ROBBERFETTED

Max. Flow Rate.....202 lpm (58 gpm)
Max. Inlet Pressure8.6 bar (125 psig)
Max. Solids Passage.....6.4 mm (1/4")
Max. Suction Lift.....6.9 m Dry (22.3')
9.0 m Wet (29.5')



PS220/PS230 METAL FULL-STROKE PTFE-FITTED

Max. Flow Rate.....197 lpm (52 gpm)
Max. Inlet Pressure8.6 bar (125 psig)
Max. Solids Passage.....6.4 mm (1/4")
Max. Suction Lift.....5.2 m Dry (17.0')
9.0 m Wet (29.5')

